



lumii

FLUTE COLOURS









Cloud 223

Barley 440

Oyster 237

Oatmeal 610

Plaster 606










Palladian 232

Smoke 236

Dusk 233

Cardinal 445

SCHEMATIC





- Flute panels are designed for continuous vertical installation
- Align panels side-by-side with consistent spacing or tight butt joins
- Begin installation from the most prominent wall or central feature to maintain visual balance
- If installing around corners, start from the corner and work outwards to retain pattern flow

FLUTE SPECIFICATIONS



COMPOSITION

100% PET (75% Post Consumer Recycled Waste, 25% Polyester Felt)



COLOURS

Available in any 12mm colour, with 9 UK-stocked shown above



DIMENSIONS

2740mm (+/- 3mm) x 1110mm (+/- 3mm) Thickness: 8mm (+/-0.5mm) Weight: 8kg



FIRE & HEAT

Fire retardant: EN 13501-1: 2018 Classification B-s1, d0 P Melting Point 250°C Max. Recommended Service Temp: Up to 80°C



Miixfelt™ ACOUSTIC RESULTS

Aw

Class E. 0.25 (50mm air gap) Class C. 0.65 (50mm air gap) Class A 0.90 (100mm air gap) Class A. 0.95 (200mm air gap) AS Coefficient @ 2000 Hz 0.85 (0mm air gap)

0.85 (0mm air gap) 1 (50mm air gap) 1* (100mm air gap) 1 (200mm air gap) SAA (NRC)

0.41 (0mm air gap) 0.76 (50mm air gap) 0.87 (100mm air gap) 0.92 (200mm air gap)

For technical support or further advice, contact:

hello@lumii.design | +44 (0)1273 750 240



