

Miixfelt Acoustic 9mm Panel Specification Sheet

Product Name: Miixfelt

Panel Composition: 100% PET (50% Post Consumer Recycled Waster 50% Polyester Felt)

Panel Dimension : 2440mm (+/- 3mm) x 1220mm (+/- 3mm)

Thickness: 9mm (+/-0.5mm)

Weight: 5.7kg per Panel Material

Colours: 18 Colours in Stock / 40 Colours Available

Melting Point: 250°C Max. Recommended Service Temp: 80°C

aw 0.25 (0mm air gap) Class E. 0.65 (50mm air gap) Class C. 0.90 (100mm air gap) Class A. 0.90 (200mm air gap) Class A

NRC: 0.35 (0mm air gap) 0.75 (50mm air gap)

Fire retardant: EN 13501-1: 2018 Classification B-s1, d0 P

UK Processing & Fabrication Service

Miixfelt Acoustic 9mm Panel Specification Sheet

ENVIRONMENTAL

Miifelt PET is manufactured using a minimum of 50% post-consumer recycled content (PET plastic bottles).

HAZARDS IDENTIFICATION

Non-hazardous and non-dangerous goods.

CHEMICAL ENTITY

Polyester Fiber from PET (Polyethylene Terephthalate).

Key Features

- OEKO-TEX Standard 100 - Declaration of conformity EN ISO 170050-1
 - Manufactured using a minimum of 50% post-consumer recycled material.
 - Limitless branding and design possibilities with in-house custom cutting.
 - Excellent acoustic performance.
 - 0% Formaldehyde binders in our Mixfelt Products.
 - Non-toxic, non-irritant and non-allergenic.
 - Extensive range of colours Manufactured and stocked in the uk.
-

UK Processing & Fabrication Service