

# Miixfelt Acoustic 24mm Panel Specification Sheet

Product Name: Miixfelt

---

Panel Composition: 100% PET (50% Post Consumer Recycled Waster 50% Polyester Felt)

---

Panel Dimension : 2800mm (+/- 3mm) x 1200mm (+/- 3mm)

---

Thickness: 24mm (+/-0.5mm)

---

Weight: 16kg per Panel Material

---

Colours: 40 Colours Available

---

Melting Point: 250°C Max.

---

Recommended Service Temp: 80°C

---

NRC: 0.45 (0mm air gap) 0.70 (25mm air gap) 0.85 (50mm air gap)

---

Fire retardant: EN 13501-1: Classification B-s1, d0 P

---

UK Processing & Fabrication Service

# Miixfelt Acoustic 24mm Panel Specification Sheet

## ENVIRONMENTAL

Miifelt PET is manufactured using a minimum of 50% post-consumer recycled content (PET plastic bottles).

---

## HAZARDS IDENTIFICATION

Non-hazardous and non-dangerous goods.

---

## CHEMICAL ENTITY

Polyester Fiber from PET (Polyethylene Terephthalate).

---

## Key Features

- Manufactured using a minimum of 50% post-consumer recycled material.
  - Limitless branding and design possibilities with in-house custom cutting.
  - Excellent acoustic performance.
  - 0% Formaldehyde binders in our Mixfelt Products.
  - Non-toxic, non-irritant and non-allergenic.
  - Extensive range of colours Manufactured and stocked in the uk.
- 

UK Processing & Fabrication Service